
INSTALLATION INSTRUCTIONS

PART NUMBER: SPN002939

DESCRIPTION: Crosstrek Front Bumper Under Guard

KIT CONTENTS:





Front Bumper Under Guard x 1




Retainer Plug x 3 Alcohol Wipe x 1

TOOLS REQUIRED:







Masking Tape

MEANING OF CHARACTERS:



: Remove



: Tightening Torque



: Install



: Loosen



: Disconnect



: Discard



: Connect



: Reuse




: Location of Clip or Screw

DESCRIPTION
Crosstrek Front Bumper Under Guard


ISSUE	
01	

Surface Preparation




Make sure that all installation surfaces are clean, free of dirt, grease and debris using soap and water solution. Clean the indicated tape adhesion area with the alcohol wipe (provided).

Front Bumper Under Guard Installation




Identify the (3) locations of the factory retainers in underside of bumper and remove with either Philips head screwdriver or plastic pry bar. Discard the 3 retainers.




Peel back approx. 50mm / 2" of tape liner at each end of the part and fold at 45 degrees to part. Tape peeled back section of tape liner to outside surface of the bumper under guard using masking tape.


DESCRIPTION	ISSUE	DATE	SUBARU OF AMERICA	PAGE
Crosstrek Front Bumper Under Guard	01	15-05-17	SUBARU OF AMERICA	2/4



Install Front Bumper Under Guard in position of best fit ensuring that folded tape liners remains outside.




Install (3) provided replacement retainer plugs in (3) available holes in Front Bumper Under Guard.




Apply moderate forward pressure towards bumper for product best fit, then apply pressure to the ends of the Front Bumper Under Guard where the double sided tape liner has been removed, (as shown).

DESCRIPTION	ISSUE	DATE	SUBARU OF AMERICA	PAGE
Crosstrek Front Bumper Under Guard	01	15-05-17	SUBARU OF AMERICA	3/4



While applying moderate forward pressure towards bumper, pull exposed tape liners towards opposite end of Front Bumper Under Guard, one side at a time (as shown).



With a clean, dry microfiber towel, apply pressure to taped surface of Front Bumper Under Guard, (as shown) going from side to side approx. 5 times to ensure proper tape adhesion is achieved.

DESCRIPTION
Crosstrek Front Bumper Under Guard